10ZiG TECHNOLOGY
Thin Client Technology At Its Peak

Part Number: 5872v, 5817v, 5818v

5800 Series Thin Clients for VDI
Performance Class

The 5800 Series Thin Clients are well suited for every user type from advanced to task worker to the most hostile manufacturing environment. This Series encompasses high-performance and versatility in the best form factor available in today's marketplace. Whether doing published applications or a full VDI implementation, the 5800 Series has you covered. The units are designed to be eco-friendly while still delivering a robust VDI experience to the end-user. The 5800 Series ultimately brings increased productivity and ease of use to any desktop. Available in PEAKOS (Linux), WES7 and WE8.

► WE8 NOW AVAILABLE	► Dual DVI Monitor Support STD
► Ultra-mini form factor	► Optional 802.11 a/b/g/n Wireless
► VMware & Citrix Ready	► VESA Mounting Capable
► Intel Atom Dual Core Processor	► Free Centralized Management

vmware READY · teradici PCoIP · CITRIX ready · HDX · Quest vWorkspace READY · 2X · redhat · IBM Virtual Desktop VirtualBridges · ENERGY STAR

Americas	P: 866-865-5250	E: info@10ZiG.com	W: www.10ZiG.com
EMEA	P: +44 (0) 116 214 8650	E: info@10ZiG.eu	W: www.10ZiG.eu
APAC	P: 1300 768 799	E: info@10ZiG.com.au	W: www.10ZiG.com.au

Learn More

5800 Series Thin Clients for VDI

System	
Management	10ZiG Centralized Management Utility
Form Factor	Ultra Mini
Processor	Intel Atom D2550 Dual Core 1.86GHz
Chipset	Intel NM10 Integrated Graphics Media Accelerator 3650
Dimensions	
Device	1.7"(W) x 7.8"(H) x 5.1"(D) - 42mm x 198mm x 140mm
Weight	2.53 lbs (1.15kg)
Connections	
Ports	USB x 5, Mic-In x 1, Line-Out x 1, PS2 x 1, RJ-45 LAN, DC Jack x 1
Video/Audio	DVI-I x 1 (VGA Supported with Included Adapter), DVI-D x 1, 1920 x 1200
Networking	
Wireless	Optional (Internal USB header and mini PCIe socket for WLAN module)
Ethernet	10/100/1000 Base-T
Environmental	
Operating Temp.	32-95F (0-35C), 20-80% non-condensing humidity
Power	12 Watt Consumption, 36 Watt, DC-12V/3A External Power Adapter

WARRANTY: All Thin Clients include a 3-Year Advanced Exchange Warranty

Specifications

1. Power Button/Power HDD LED
2. Front USB (2)
3. Mic In
4. Line Out
5. Secure USB (1)
6. Back USB (2)
7. Ethernet -RJ45 LAN port
8. PS2 port
9. DVI-D
10. DVI-I
11. DC Jack
12. Kensington Lock

	5872v	5817v	5818v
Operating System	10ZiG PEAKos (Linux)	WES7	WE8
Memory			
RAM	MIN: 1GB MAX: 2GB	MIN: 2GB MAX: 4GB	MIN: 2GB MAX: 4GB
Storage	MIN: 1GB MAX: 2GB	MIN: 16GB MAX: 64GB	MIN: 16GB MAX: 64GB
Software			
Software Applications	Firefox, Citrix Receiver, RDP, VNC	Internet Explorer, Citrix Receiver, RDP, VNC	Internet Explorer, Citrix Receiver, RDP, VNC
VDI Connection Brokers Supported	Citrix XenDesktop w/ HDX, VMware Horizon View w/ PCoIP, VDI-In-a-Box, Red-Hat, 2X, Quest vWorkspace	Citrix XenDesktop w/ HDX, VMware Horizon View w/ PCoIP, VDI-In-a-Box, Red-Hat, 2X, Quest vWorkspace, Remote FX	Citrix XenDesktop w/ HDX, VMware Horizon View w/ PCoIP, VDI-In-a-Box, Red-Hat, 2X, Quest vWorkspace, Remote FX